



**Feature**

- 1. **1.5x8 dots includes cursor**
- 2. Built-in controller(ST7066U or equivalent)
- 3. +5V power supply(Also available for +3.3V)
- 4. 1/16duty cycle
- 5. B/L can be driven by pin15,16 or A and K

**Terminal Function**

Pin	Symbol	Function
1	V <sub>SS</sub>	GND
2	V <sub>DD</sub>	Supply voltage for logic
3	V <sub>0</sub>	Contrast Adjustment
4	RS	Register select signal
5	R/W	Read / write signal
6	E	Enable signal
7	DB0	Data bus line
8	DB1	Data bus line
9	DB2	Data bus line
10	DB3	Data bus line
11	DB4	Data bus line
12	DB5	Data bus line
13	DB6	Data bus line
14	DB7	Data bus line
15	A	Backlight LED+
16	K	Backlight LED-

**Mechanical Data**

Item	Value
Outline (mm)	85.0*36.0*13.2MAX
Viewing Area (mm)	66.0*16.0
Active Area (mm)	56.2*11.5
Dot Size (mm)	0.55*0.65
Dot Pitch (mm)	0.6*0.7

**Electrical Characteristics**

Item	Symbol	Min	Typ	Max
Operating Voltage(V)	V <sub>DD</sub>	4.7	5	5.3
Supply Voltage For LCD	V <sub>DD</sub> -V <sub>0</sub>	-	4.4	-
Input High Voltage(V)	V <sub>IH</sub>	0.7 V <sub>DD</sub>	-	V <sub>DD</sub>
Input Low Voltage(V)	V <sub>IL</sub>	V <sub>SS</sub>	-	0.6
Operating Current(mA)	I <sub>DD</sub>	-	1.2	1.5

**Backlight Characteristics**

Item	Symbol	Min	Typ	Max
Forward Voltage (V)	V <sub>F</sub>	—	5	--
Forward Current (mA)	I <sub>F</sub>	—	32	40

**Absolute Maximum Rating**

Item	Symbol	Min	Max
Power Supply(V)	V <sub>DD</sub> -V <sub>SS</sub>	-0.3	7
Operating Temperature(°C)	Top	-20	70
Storage Temperature(°C)	T <sub>st</sub>	-30	80