



ROSH


Revision	Dispersion	Date	Signed
01	First	2023.03.06	YP



1	VBL-	31	R3
2	VBL-	32	R4
3	VBL+	33	R5
4	VBL+	34	R6
5	Y1	35	R7
6	X1	36	HSYNC
7	NC	37	VSYNC
8	RESET	38	DCLK
9	SPENA	39	NC
10	SPCLK	40	NC
11	SPDAT	41	VCC
12	B0	42	VCC
13	B1	43	Y2
14	B2	44	X2
15	B3	45	NC
16	B4	46	NC
17	B5	47	NC
18	B6	48	NC
19	B7	49	NC
20	G0	50	NC
21	G1	51	NC
22	G2	52	DE
23	G3	53	GND
24	G4	54	GND
25	G5		
26	G6		
27	G7		
28	R0		
29	R1		
30	R2		

NOTES:

1. DISPLAY TYPE: 3.5" TFT, TRANSMISSIVE
2. DRIVER IC: NV3052C
3. VIEWING DIRECTION: All 0'Clock
4. BACKLIGHT: 6 pcs White LED
5. INPUT CURRENT: VCC 3.3V (type)
6. OPERATING TEMP: -20°C ~ +70°C
7. STORAGE TEMP: -30°C ~ +80°C
8. UNDEFINED DIMENSION TOLERANCE: ±0.2mm
9. ROHS COMPLIABLY



深圳市华之洋光电科技有限公司

Shenzhen HZY Photoelectric Technology Co., Ltd

Customer Ref.	Model No.	Drawing Title	Material	Unmarked Tolerance	Unit	Scale	Page
---	Approve	HZ035LPCS07-B0	LCM	±0.2	mm	--	1 of 1
Part No.	Checked	Draw	YP	Date	2023.03.06	Rev 00	
Drawing No.	---						